

Separator walls

- for separating junction casings from electrical circuit
- can be retrofitted
- Halogen-free



for casing size	180 x 180 mm	250 x 220 mm
Art.-No.	1296-20	1297-20
Inner packaging/shipping	10 / -	10 / -

Cover

- flat cover edge
- surface roughened
- countersunk for screw heads




For casing size - concrete construction boxes	128 x 128 mm	180 x 180 mm	250 x 220 mm
For casing size - flush-mounting boxes	107 x 107 mm	159 x 159 mm	238 x 208 mm
For casing size - cavity wall boxes	105 x 105 mm	165 x 165 mm	235 x 205 mm
Fireproof	850 °C	850 °C	850 °C
Art.-No.	1095-93	1096-93	1097-93
Inner packaging/shipping	10 / 500	10 / 200	5 / 100

Universal VDE cover

- for all one-gang, one-gang junction and junction boxes
- with central exit for light hook
- flat cover edge
- surface roughened



Diameter	92 mm	92 mm
Screw spacing	60 / 67 mm	60 / 67 mm
Fireproof	850 °C	850 °C
Halogen-free	-	Yes
	Yes	Yes
Art.-No.	1184-90	1184-77
Inner packaging/shipping	25 / 250	25 / 250

Universal waterproof cover

- central entry with stoppers
- for countersunk screws Ø 4 mm



Diameter	90 mm	90 mm
Screw spacing	67 mm	60 mm
Fireproof	850 °C	850 °C
Halogen-free	Yes	Yes
Art.-No.	1174-99	1174-98
Inner packaging/shipping	10 / -	10 / -

End covers and separator walls

for on-site mixed concrete

Plug-in cover

- With central plug-in connector
- For mounting wood screw Ø 3.5 mm, head Ø 6.5 - 7 mm, attach centrally in cover exit
- Screw not included



Height	5 mm
Diameter	98 mm
Colour	RAL 9010
 850 °C / 	Yes / Yes
	Yes
Art.-No.	11081
Inner packaging/shipping	- / 10

Plug-in cover with cable outlet

- With central plug-in connector
- For Art. Nos. 1245-60/-62/-63 and 1246-57
- For mounting wood screw Ø 3.5 mm, head Ø 6.5 - 7 mm, attach centrally in cover exit
- Screw not included



Height	5 mm	22 mm
Diameter	98 mm	80 mm
Colour	RAL 9010	RAL 9010
 850 °C / 	Yes / Yes	Yes / Yes
	Yes	Yes
Art.-No.	11082	11088
Inner packaging/shipping	- / 10	- / 10

Cover with mounting ring

- Can also be used as cover for reserve conduit exits
- Attach the mounting ring (included) to the exit and place the end cover in position (bayonet fitting)
- For Art. Nos. 1245-60/-62/-63 and 1246-57



Height	15 mm
Outer diameter	100 mm
Art.-No.	10100
Inner packaging/shipping	- / 10

Conduit and cable distance support

- Fixing to the formwork using expanding dowels, nails or screws
- Halogen-free



For fixing cable and conduit to formwork	Yes	-
Conduit and cable distance piece for 1270-00	-	Yes
Art.-No.	1270-00	9060-95
Inner packaging/shipping	- / 1000	1000 / 30000

Plug-in cover

- Break-out openings for cables and light fitting support hooks
- Plug-in depth min. 3 mm max. 15 mm



Diameter	35 mm	60 mm
Art.-No.	1148-93	1259-96
Inner packaging/shipping	25 / 100	25 / 250

Expanding dowel

- for quick fixing to steel formwork
- 1-piece in plastic
- for boxes, casings, bushes etc.
- drill hole size required Ø 5.5 mm



Diameter	5,5 mm
Art.-No.	1217-02
Inner packaging/shipping	500 / 2500

FLUSH-MOUNTING

CAVITY WALL

CONCRETE

HOUSINGS

FIRE PROTECTION

PLUGGABLE

CONNECTIVITY

CABLE GLANDS

TOOLS

SERVICE